

# SP320

## COMPACT 2-WAY LOUDSPEAKER SYSTEM



- 8" LF Vented Enclosure
- 1" Compression driver with Conical Horn
- Fly Mounting Points, Pole mount Cup and U Bracket Included
- Powering Mode: Full Range Passive
- For Touring or Permanent Installation

### Product Information

2-WAY loudspeaker designed as a dedicated top-box. It should be supported by PSUB1 or DG118 sub woofer below 100Hz. It houses 200 mm (8") Ferrite mid-woofer and 26 mm (1") Mylar driver on Conical horn. SP320 is ideal for medium and smaller clubs, dance-floors. The cabinet offers built-in flying point for both horizontal and vertical mounting. The trapezoidal cabinet allows flexible fixing and easy construction of clusters and arrays. LSS's advanced crossover includes professional protection of HF.

### Data Sheet

Frequency Response	±5 dB 60 Hz ~ 20 KHz -10 dB 50 Hz
Sensitivity (1 Watt @ 1 m) Max SPL Calculated	94 dB 118 dB
Nominal Input Impedance (Ω)	8 Ω
Power Handling (Watts Cont. AES) Peak Power	300 W 1200 W
Nominal Dispersion (@ -6 dB)	80° (H) x 80° (V)
Dimensions mm (±1 mm) (H x W x D)	420 x 306 x 345
Weight	11 Kg

### Enclosure Material

- Enclosure Material: Birch Plywood of 15 mm / MDF of 14 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 8 Point Mounting Suspension and U bracket included
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: Neutrik NL4 Speakon
- Optional Accessories: Fly Clip with Ring

INSTALL | EVENTS | PORTABLE

